

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International publication date
19 February 2004 (19.02.2004)

PCT

(10) International publication number
WO 2004/014677 A1


- (51) International patent classification⁷: B60H 1/00 (71) Applicant (for all designated States except US): BEHR GMBH & CO. [DE/DE]; Mauserstr.3, 70469 Stuttgart (DE).
- (21) International application number: PCT/EP2003/005612
- (22) International filing date: 28 May 2003 (28.05.2003) (72) Inventor; and (75) Inventor/Applicant (US only): KOUKOURAVAS, Evripidis [GR/DE]; Teckstrasse 6, 72654 Neckartenzlingen (DE).
- (25) Language of filing: German
- (26) Language of publication: German
- (30) Data relating to the priority:
102 35 513.4 29 July 2002 (29.07.2002) DE
102 61 036.3 17 December 2002 (17.12.2002) DE (74) Joint Representative: BEHR GMBH & CO.; Mauserstr.3, 70469 Stuttgart (DE).
- (81) Designated states (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DK, DM, DZ, EC, EE, ES, FI, GB, GD,

[continued on next page]

As printed

(54) Title: AIR-CONDITIONER HOUSING

(54) Bezeichnung: KLIMAGEHÄUSE



WO 2004/014677 A1

(57) Abstract: The invention relates to an air-conditioner housing comprising an evaporation device (5), a heating device (7), and a mixing chamber (23), out of which air flows to the rear footwell while serving to ventilate the rear passenger compartment. The air-conditioner housing also comprises an air control device (9) that uses mixing flaps (11, 13) to control the air flowing via the evaporation device (5) and the heating device (7) into the mixing chamber (23). The inventive air-conditioner housing is characterized by having a separate stratification duct (39) through which cool air can be guided into the area of the rear passenger compartment ventilation.

(57) Zusammenfassung: Es wird ein Klimagehäuse mit einer Verdampfungseinrichtung (5), einer Heizungseinrichtung (7), einer Mischkammer (23), aus der Luft zum Fond-Fussraum und zur Fondbelüftung strömt, und mit einer Luftsteuereinrichtung (9), die die durch die Verdampfungseinrichtung (5) und die Heizungseinrichtung (7) in die Mischkammer (23) strömende Luft mittels Mischklappen (11,13) steuert, vorgeschlagen. Dieses ist gekennzeichnet durch einen separaten Schichtungskanal (39), durch den kühle Luft in den Bereich der Fondbelüftung führbar ist.